



20' x 6'11" Maverick Gooseneck  
Standard 6'6" high for livestock  
(shown with optional hubcaps)

### MAVERICK STANDARD SPECIFICATIONS GOOSENECK MODELS

<b>Floor Length:</b>	16', 18', 20', 22', 24'
<b>Inside Height:</b>	6'6", optional 7'
<b>Exterior Width:</b>	7'0" nominal, 6'11" actual
<b>Axles:</b>	7,000# Rubber Torsion
<b>Wheels:</b>	16" Pressed Steel, 8 Hole
<b>Tires:</b>	235/85R16; Load Range E
<b>Brakes:</b>	Electric
<b>Hitch:</b>	2-5/16" Adjustable Ball Coupler
<b>Landing Gear:</b>	Single Leg, Single Speed
<b>Slats:</b>	Extruded Aluminum Outside Slat with Track for Plexiglas™. Styles A, B and C.
<b>Posts:</b>	Extruded Aluminum 1" x 3" Tubing on maximum of 18" Centers.
<b>Bottom Rail:</b>	Extruded Aluminum 12" Deep
<b>Top Rail:</b>	Extruded Aluminum with recessed light trough
<b>Crossmembers:</b>	3" Extruded Aluminum I-Beams on 12" Centers
<b>Floor:</b>	1/8" Aluminum Diamond Plate with High Diamonds and (4) Longitudinal Ridges
<b>Front Nose:</b>	.080" Aluminum Sheet with Cast Aluminum Corners, Aerodynamic Design
<b>Upper Coupler:</b>	5" x 5" x 3/16" Tubular Steel with 8" Side Rail on Gooseneck
<b>Rear Frame:</b>	Extruded Aluminum with Cast Rear Corners
<b>Partitions:</b>	(1) Approximate Center of Trailer (1) Full width Drop Down Nose Gate
<b>Side Door:</b>	33" Wide, 18" From Drop Sheet, Curbside
<b>Rear Door:</b>	Full Swing with 1/2 Sliding Pass-thru Door, Roadside
<b>Roof:</b>	One-Piece .040" Aluminum with Extruded Aluminum Hat Posts on 24" Centers
<b>Inside Lights:</b>	(2) Inside Dome Lights
<b>Rear Lights:</b>	Stop/Tail/Turn Lights, One on Each Side
<b>Wiring:</b>	ATA Color Coded, Enclosed
<b>Tire Carrier:</b>	Aluminum, Mounted on the Drop
<b>Paint:</b>	All Steel Parts Painted Grey, Aluminum is Natural.
<b>Bumper:</b>	Full Width Rubber Dock Bumper
<b>Skid Plate:</b>	(3) Skid Plates at Rear

### MAVERICK STANDARD SPECIFICATIONS BUMPER HITCH MODELS

<b>Floor Length:</b>	10', 12', 14', 16'
<b>Inside Height:</b>	6'6", optional 7'
<b>Exterior Width:</b>	7'0" nominal, 6'11" actual 6'6" nominal, 6'5" actual
<b>Axles:</b>	3,500# and 5,200# Rubber Torsion
<b>Wheels:</b>	16" Pressed Steel, 6 Hole
<b>Tires:</b>	235/75R15
<b>Brakes:</b>	Electric
<b>Hitch:</b>	2-5/16" Ball Coupler
<b>Landing Gear:</b>	Top Wind
<b>Slats:</b>	Extruded Aluminum Outside Slat with Track for Plexiglas™. Styles A, B and C.
<b>Posts:</b>	Extruded Aluminum 1" x 3" Tubing on maximum of 18" Centers
<b>Bottom Rail:</b>	Extruded Aluminum 12" Deep
<b>Top Rail:</b>	Extruded Aluminum with recessed light trough
<b>Crossmembers:</b>	3" Extruded Aluminum I-Beams on 12" Centers
<b>Floor:</b>	1/8" Aluminum Diamond Plate with High Diamonds and (4) Longitudinal Ridges
<b>Front End:</b>	.080" Aluminum Sheet with Cast Aluminum Corners, Aerodynamic Design
<b>Rear Frame:</b>	Extruded Aluminum with Cast Rear Corners
<b>Partitions:</b>	(1) Approximate Center of Trailer on 14' and 16' models. (Not Standard on 10' & 12' BH)
<b>Side Door:</b>	33" Wide, Curbside of Trailer
<b>Rear Door:</b>	Full Swing with 1/2 Sliding Pass-thru Door, Roadside
<b>Roof:</b>	One-Piece .040" Aluminum with Extruded Aluminum Hat Posts on 24" Centers
<b>Inside Lights:</b>	(2) Inside Dome Lights
<b>Rear Lights:</b>	Stop/Tail/Turn Lights, One on Each Side
<b>Wiring:</b>	ATA Color Coded, Enclosed
<b>Tire Carrier:</b>	Aluminum, Mounted on the Front
<b>Paint:</b>	All Steel Parts Painted Grey, Aluminum is Natural
<b>Bumper:</b>	Full Width Rubber Dock Bumper
<b>Skid Plate:</b>	(3) Skid Plates at Rear

### M. H. Eby, Inc.

1194 Main St., PO Box 127  
Blue Ball, PA 17506  
800/292-4752 • 717/354-4971  
Fax: 717/355-2114

4435 St. Rt. 29, PO Box 137  
West Jefferson, OH 43162  
800/752-0507 • 614/879-6901  
Fax: 614/879-6904

1708 Eby Drive, PO Box 156  
Story City, IA 50248  
866/894-3297 • 515/733-5207  
Fax: 515/733-5262

Distributed By

