



LS SERIES

The versatile and affordable Maverick LS Series provides small to mid-size farm, ranch and livestock operations the benefits of Eby's all-aluminum trailers. Each Maverick LS features a reduced width (6' 5" for bumper hitch models, 6' 11" for goosenecks) to improve visibility and handling...ideal for pulling with lighter duty trucks or SUV's. Eby's design experience with strong, lightweight aluminum gives you dependable product service and improved fuel economy.

Engineered for durable performance for a wide range of livestock, these trailers are built without compromise to Eby's rugged all-aluminum construction. Production economies make Maverick LS prices very attractive, so even the occasional user can afford the added benefits of low-maintenance aluminum with its longer life and higher resale value.



16' L x 6'5" W x 6'6" H Bumper Hitch
(also available in 7' height)



13' L x 6'5" W Bumper Hitch
(shown in optional 7' inside height)

Maverick LS Bumper Hitch Trailers

STANDARD SPECIFICATIONS

Floor Lengths: 13' and 16'

Inside Heights: 6'6" or 7'

Exterior Width: 6'5"

Axles: Rubber Torsion Ride with Electric Brakes.
3.5K on 13', 5.2K on 16'

Wheels: 16" Pressed Steel

Tires: 235/85R16 Steel Belted Radials

Hitch: 2-5/16" Coupler

Landing Gear: Top Wind

Slats: Extruded Aluminum Outside Slat with Track for Plexiglas. Slat Options: (2) 8" Openings at Top with (1) 2" Opening 20" Off Floor. Also Available with (2) 8" Openings at Top Only.

Side Posts: Extruded Aluminum 1" x 3" Tubing on Maximum of 21" Centers

Bottom Rail: Extruded Aluminum 12" Deep

Top Rail: Extruded Aluminum with Recessed Light Trough

Crossmembers: 3" J-Beams on 12" Centers

Floor: .125" Flat Aluminum Diamond Plate

Front End: .080" Aluminum Sheet with Cast Aluminum Corners

Rear Frame: Extruded Aluminum with Cast Rear Corners

Rear Door: Full Swing with Roadside 1/2 Sliding Pass-Thru Door, (2) 4" Hinges

Center Partition: Corrugated Panel with Single Row of Punched Air Openings, Outside Release (Center Partition Optional on 13' Model Length)

Side Door: Passenger Side, 29" Wide

Roof: One-Piece .040" Aluminum with Extruded Aluminum Hat Posts, Roof Riveted to Top Rails on 4" Centers

Inside Lights: (1) Sealed Beam Dome Light, Switch on Roadside Rear

Lights: (per D.O.T. Requirements)

Rear- Stop/Tail/Turn Lights, One on Each Side, Cluster of (3) on Center Rear Header

Front- (1) Amber Each Corner, Cluster of (3) on Center Top

Wiring: ATA Color Coded

Tire Carrier: Aluminum, Mounted on the Front

Paint: All Steel Parts Painted Grey, Aluminum Is Natural.

Bumper: Full Width Rubber Dock Bumper

Skid Plates: (2) Skid Plates at Rear

