



RUFF NECK

24'L x 8'W Ruff Neck Gooseneck
Standard 6'6" high for livestock

RUFF NECK STANDARD SPECIFICATIONS

Floor Length: 20', 22', 24', 26', 28', 30', 32'

Inside Height: Std. 6'6"; opt. 7', 7'6", 8'

Axles: 8,000 lb. rubber ride, 3-3/8" brake, (20'-26' lengths) 10,000 lb. rubber ride, 4" brake, (28'-32' lengths)

Wheels: Heavy-duty 17.5" steel, 8-hole

Tires: 9R17.5 steel belted radials, 16 ply rating (20'-26' lengths) 235/75R17.5 steel belted radials, 16 ply rating (28'-32' lengths)

Running Gear

Brakes: Electric, both axles (electric over hydraulic as option)

Hitch: Adjustable 2-5/16" ball coupler with steel hitch post section

Landing Gear: Single crank leg landing gear

Box Construction

Slats: Extruded aluminum outside slats with track for plexiglass closures, posts inside. Standard slat spacing with a choice of 3 patterns: two 6" openings at top; one 2" opening 18" off floor; two 6" openings top; three 4" openings top, two 2" openings bottom

Posts: Extruded aluminum tubing on 18" centers

Bottom Rails: Extruded aluminum, 12" deep

Top Rails: Extruded aluminum with recessed light trough

Crossmembers: 3" extruded aluminum I-beams on 12" centers

Floor: 1/8" 6061 high tread plate floor, longitudinally ridged for strength and traction. Smooth floor in nose

Front Nose Assembly: .080" aluminum sheet with aerodynamic cast aluminum corner caps

Upper Coupler Assembly: 5" x 7" tubular steel with 14" deep aluminum side rail

Rear Frame Assembly: Extruded aluminum, fully welded, with cast aluminum corners

Partitions

Center Partition: Hinged at front of wheel pockets. Aluminum tube and sheet construction with outside release standard

Front Partition: Full drop down gate in nose. Aluminum post and sheet construction

Side Door & Rear Door Assembly

Side Access Door: 33" wide curb side door, 18" from front. Side door cut-out 4-1/4" above floor level. Other locations and flush to floor entry available as option

Rear Door: Fully swing with slider door on driver side (Roll-up door available as option)

Roof Assembly

Sheet: One-piece .040" aluminum, tensioned and riveted around entire perimeter

Bows: Arched, extruded aluminum hat sections on 24" centers

Lights & Wiring

Lights: 12-volt, D.O.T. approved; all lights sealed beam

Wiring: A.T.A. color coded, enclosed, externally accessible

Rear Lights: Modular, turn-tail-stop. One light each side (red)

Inside Lights: Two, with external rear recessed waterproof switch

Miscellaneous

Tire Carrier: Aluminum, mounted on front of trailer

Wheel Pockets: Combination of smooth aluminum sheet and heavy-duty extruded aluminum axle rail, fitted flush to prevent dirt buildup

Paint: Aluminum parts natural; steel parts painted gray

Rear Bumper: Full width, molded rubber dock bumper

M. H. Eby, Inc.

1194 Main St., PO Box 127
Blue Ball, PA 17506
800/292-4752 • 717/354-4971
Fax: 717/355-2114

4435 St. Rt. 29, PO Box 137
West Jefferson, OH 43162
800/752-0507 • 614/879-6901
Fax: 614/879-6904

1708 Eby Drive, PO Box 156
Story City, IA 50248
866/894-3297 • 515/733-5207
Fax: 515/733-5262

Distributed By

